

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C12Q 1/68, C12M 1/00, 1/40, C12P 19/34, G01N 21/77, 21/00, 21/29, 21/27, 27/26, C25D 17/00	A1	(11) International Publication Number: WO 97/39144 (43) International Publication Date: 23 October 1997 (23.10.97)
(21) International Application Number: PCT/US97/05534 (22) International Filing Date: 3 April 1997 (03.04.97) (30) Priority Data: 08/634,073 17 April 1996 (17.04.96) US (71) Applicant (for all designated States except US): MOTOROLA INC. [US/US]; 1303 East Algonquin Road, Schaumburg, IL 60196 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): ACKLEY, Richard [US/US]; 317 Goat Hill Road, Lambertville, NJ 08530 (US). SHIEH, Chan-Long [US/US]; 6739 East Bar Z Lane, Paradise Valley, AZ 85253 (US). (74) Agents: TOLER, Jeffrey, G. et al.; Motorola Inc., Intellectual Property Dept., 1303 East Algonquin Road, Schaumburg, IL 60196 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: INTEGRATED OPTICAL MOLECULAR DETECTION DEVICE AND METHOD THEREFOR (57) Abstract A substrate (12) defines a binding site (14) for receiving a molecular receptor (16). A light source (18) and an optical detector (20) are incorporated in the substrate (12). The light source (18) illuminates the binding site (14) through the substrate (12) to produce an optical indication of a molecule (19) hybridized to the molecular receptor (16). The optical detector (20) detects the optical indication through the substrate (12). Preferably, the substrate (12) defines a first side on which the binding site is defined, and a second side opposite the first side on which the light source and the optical detector are integrated. A transparent electrode can be included at the binding site for field-assisted hybridization and de-hybridization.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	R	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

0

5

10

INTEGRATED OPTICAL MOLECULAR DETECTION
DEVICE AND METHOD THEREFOR

Field of the Invention

15

The present invention relates to optical molecular detection devices and methods of detection therefor.

Background of the Invention

20

Recently, an increased effort has been directed toward the development of chips for molecular detection. In general, a molecular detection chip includes a substrate on which an array of binding sites is arranged. Each binding site (or hybridization site) has a respective molecular receptor which binds or hybridizes with a molecule having a predetermined structure. A sample solution is applied to the molecular detection chip, and molecules in the sample bind or hybridize at one or more of the binding sites. The particular binding sites at which hybridization occurs are detected, and one or more molecular structures within the sample are subsequently deduced.

25

30

Of great interest are molecular detection chips for gene sequencing. These chips, often referred to as DNA

0 chips, utilize an array of binding sites each having
respective single-stranded DNA probes. A sample of single-
stranded DNA fragments, referred to as target DNA, is
applied to the DNA chip. The DNA fragments attach to one
or more of the DNA probes by a hybridization process. By
5 detecting which DNA probes have a DNA fragment hybridized
thereto, a sequence of nucleotide bases within the DNA
fragment can be determined.

To hasten the hybridization process, a local
concentration of target DNA can be increased at
10 predetermined sites using electric field enhancements.
Here, each site has an electrode associated therewith for
selectively generating an electric field thereby. The
electric field is generated by applying an electric
potential between an electrode at the site and a counter
15 electrode at a peripheral portion of the chip. To attract
DNA fragments to the site, the polarity of the electric
potential is selected to generate an electric field having
a polarity opposite to the charge of the DNA fragments. To
de-hybridize the site, an electric field having the same
20 polarity as the DNA fragments can be generated to repel the
DNA fragments from the site.

Various approaches have been utilized to detect a
hybridization event at a binding site. In one approach, a
radioactive marker is attached to each of a plurality of
25 molecules in the sample. The binding of a molecule to a
molecular receptor is then detectable by detecting the
radioactive marker.

Other approaches for detection utilize fluorescent
labels, such as fluorophores which selectively illuminate
30 when hybridization occurs. These fluorophores are
illuminated by a pump light source external to the
substrate. An external charge-coupled device (CCD) camera
is utilized to detect fluorescence from the illuminated
fluorophores.

0 An optical-detection-based DNA chip is disclosed in
"Real-time detection of DNA hybridization and melting on
oligonucleotide arrays by using optical wave guides",
Proceedings of the National Academy of Sciences, Vol. 92,
pp. 6379-6383. This DNA chip utilizes a glass substrate
5 having a surface which defines the binding sites. The
glass substrate has an end adjacent to the surface into
which light is injected by an external light source. An
external CCD camera is utilized to detect scatter light at
the binding sites at which hybridization occurs.

10

Brief Description of the Drawings

 The invention is pointed out with particularity in
the appended claims. However, other features of the
15 invention will become more apparent and the invention will
be best understood by referring to the following detailed
description in conjunction with the accompanying drawings
in which:

 FIG. 1 is a block diagram of an embodiment of an
20 integrated molecular detection device in accordance with
the present invention;

 FIG. 2 is a schematic cross-sectional view of an
embodiment of an integrated molecular detection device in
accordance with the present invention;

25 FIG. 3 is a flow chart of an embodiment of a method
of detecting hybridization of a molecule to a molecular
receptor;

 FIG. 4 is a schematic perspective view of a preferred
embodiment of an integrated molecular detection chip in
30 accordance with the present invention; and

 FIG. 5 is a schematic cross-sectional view of the
preferred embodiment of the integrated molecular detection
chip.

0 Detailed Description of a Preferred Embodiment

Embodiments of the present invention advantageously provide an integrated molecular detection device that incorporates binding sites, a light source, and optical
5 detection electronics onto a single chip. A preferred embodiment utilizes a micromachined glass substrate, a polymer light-emitting diode light source, and a thin-film-transistor-based optical imager to provide a fully integrated chip. By further including transparent
10 electrodes proximate to the binding sites, the device can perform field-enhanced hybridization and de-hybridization. Embodiments of the present invention can be utilized for DNA sequencing and detection applications.

FIG. 1 is a block diagram of an embodiment of an
15 integrated molecular detection device 10 in accordance with the present invention. The integrated molecular detection device 10 includes a substrate 12 which defines a binding site 14 for receiving a molecular receptor 16. In general, the molecular receptor 16 is selected in dependence upon
20 the type of molecule which is to be detected. The molecular receptor 16 typically includes a biological or synthetic molecule that has a specific affinity to the molecule to be detected. For DNA sequencing and/or detection applications, the molecular receptor 16 includes
25 at least one DNA probe having a specific base pair sequence. It is noted that embodiments of the present invention are not limited to detecting hybridization of DNA molecules. For example, embodiments of the present invention can be utilized to detect antibody-antigen
30 binding events.

A light source 18 is integrated in the substrate 12. The light source 18 illuminates the binding site 14 through the substrate 12 to produce an optical indication of a molecule 19 hybridized or bound to the molecular receptor

0 16. The optical indication can be provided, for example,
by a fluorophore that selectively illuminates when
hybridization occurs.

An optical detector 20 is also integrated in the
substrate 12. The optical detector 20 detects the optical
5 indication through the substrate 12, and hence detects the
hybridization or the binding of the molecule 19.

In a preferred embodiment, the substrate 12 is formed
of glass so that the binding site 14 can be illuminated
through the substrate 12, and so the optical indication can
10 be detected through the substrate 12. In general, the
substrate 12 can be formed of a substantially-transparent
material to allow illumination and detection therethrough.

FIG. 2 is a schematic cross-sectional view of another
embodiment of an integrated molecular detection device in
15 accordance with the present invention. The integrated
molecular detection device includes a substrate 30 which
can be formed of glass. The substrate 30 defines a first
side 32 (or a top side) and a second side 34 (or a reverse
side). As illustrated, the first side 32 opposes the
20 second side 34 in this embodiment.

A binding site 36 for receiving a molecular receptor
37 is defined on the first side 32 of the substrate 30.
The binding site 36 can be formed by etching or
micromachining a well into the substrate 30. The molecular
25 receptor 37 is deposited into the binding site 36 using a
robotic dispensing technique, a self-assembly technique, or
other techniques known in the art. For DNA sequencing
and/or detection applications, the molecular receptor 37
includes a chain of at least one nucleotide for detecting a
30 molecule having a complementary chain of at least one
nucleotide. Here, the molecular receptor 37 can include at
least one DNA probe which selectively hybridizes with
predetermined DNA molecules.

0 A light source 38 is incorporated on the second side
34 of the substrate 30. In a preferred embodiment, the
light source 38 includes a polymer light-emitting diode
fabricated on the second side 34 of the substrate 30.

5 The binding site 36 is illuminated by the light
source 38 through the substrate 30. In other words, light
generated at the second side 34 of the substrate 30 (by the
light source 38) is transmitted through the substrate 30 to
the binding site 36 at the first side 32. Illuminating the
binding site 36 acts to illuminate an optical indicator of
10 a molecule which has hybridized to the molecular receptor
37. Illuminating the optical indicator acts to produce an
optical indication of the hybridization.

 The optical indicator can be provided by a
fluorophore that selectively activates when hybridization
15 occurs. Here, the light source 38 preferably has an
spectral output corresponding to absorption bands of the
fluorophore. The number of fluorescent molecules can be
increased by attaching multiple fluorescent molecules to a
bead or like member which is attached to the molecule. It
20 is noted, however, that embodiments of the present
invention are not limited to the use of fluorescent
indicators, and that other optical indicators can be
utilized for the same purpose.

 An optical detector 40 is incorporated on the second
25 side 34 of the substrate 30 to detect the optical
indication. The optical detector 40 can include a
photodiode fabricated on the second side 34 of the
substrate 30. The optical detector 40 detects the optical
indication, and hence detects the hybridization of the
30 molecule, through the substrate 30. In other words, the
optical indication generated at the first side 32 of the
substrate 30 is transmitted through the substrate 30 to the
optical detector 40 at the second side 34.

0 In the embodiment of FIG. 2, the light source 38 and
the optical detector 40 are located beside one another on
the second side 34 of the substrate 30. To screen the
optical detector 40 from light emitted by the light source
38, the integrated molecular detection device includes a
5 filter 42 incorporated over the optical detector 40. Here,
the filter 42 can include a color filter to screen out
fluorescent light emanating from the light source 38.

Optionally, the integrated molecular detection device
includes a transparent electrode 44 incorporated in the
10 substrate 30 at a location proximate to the binding site
36. The transparent electrode 44 is utilized for field-
assisted hybridization and de-hybridization of the molecule
with the molecular receptor 37. Because of its
transparency, the transparent electrode 44 allows the
15 optical indication to be illuminated and detected at the
second side 34 of the substrate 30.

FIG. 3 is a flow chart of an embodiment of a method
of detecting hybridization of a molecule to a molecular
receptor. Preferably, the method is utilized in
20 conjunction with a molecular detection device as described
herein. It is noted, however, that the method may also be
utilized for detecting hybridization in other devices.

As indicated by block 50, the method includes a step
of providing a substrate which defines a binding site for
25 receiving the molecular receptor. The substrate can be
provided within a molecular detection device, such as
embodiments of the molecular detection device described
herein. As described earlier, the substrate is formed of a
material, such as glass, which allows a transmission of
30 light therethrough.

As indicated by block 52, the method includes an
optional step of generating an electric field using a
transparent electrode proximate to the binding site. The
electric field is generated to attract molecules to the

0 binding site to enhance hybridization to the molecular receptor.

As indicated by block 54, a step of illuminating the binding site through the substrate is performed to produce an optical indication of a molecule which has hybridized to
5 the molecular receptor. If a transparent electrode is included, the binding site and the optical indication are illuminated through the transparent electrode. As described earlier, the binding site can be illuminated from a side of the substrate opposite to a side on which the
10 binding site is defined. The binding site can be illuminated by a light source, such as a light-emitting diode, fabricated into the substrate.

As indicated by block 56, a step of detecting the optical indication through the substrate is performed. If
15 a transparent electrode is included, the optical indication is detected through the transparent electrode. The optical indication can be detected from a side of the substrate opposite to the side on which the binding site is defined. The optical indication can be detected by an optical
20 detector, such as a photodiode, fabricated on the substrate.

As indicated by block 58, the method includes an optional step of generating an electric field using the transparent electrode to de-hybridize the molecule from the
25 molecular receptor.

FIG. 4 is a schematic perspective view of a preferred embodiment of an integrated molecular detection chip in accordance with the present invention. The integrated molecular detection chip includes a substrate 60 which
30 defines a plurality of binding sites 62. The plurality of binding sites 62 are formed by wells 64 etched on a top surface 66 of the substrate 60. The plurality of selective binding sites 62 are arranged as a matrix in this

0 embodiment. In alternative embodiments, the plurality of binding sites 62 can be arranged as another type of array.

FIG. 5 is a schematic cross-sectional view of the preferred embodiment of the integrated molecular detection chip. Specific DNA receptors 70 having specific base pair
5 sequences are deposited into the wells 64. The specific DNA receptors 70 can be deposited using techniques which include, but are not limited to, robotic dispensing techniques and self-assembly techniques.

Integrated into the substrate 60 below each of the
10 plurality of binding sites 62 is a respective one of a plurality of optical detectors 72. Each of the plurality of optical detectors 72 includes an a-Si photodiode fabricated into a bottom surface 74 of the substrate 60. The plurality of optical detectors 72 can be matrix
15 addressed using a-Si or poly-Si thin-film transistors to form an imaging array with a one-to-one correspondence to the binding sites 62.

Between each adjacent pair in a row of the plurality of optical detectors 72 is a respective one of a plurality
20 of light sources 76 integrated into the substrate 60. Each of the plurality of light sources 76 includes a polymer light-emitting diode fabricated into the bottom surface 74 of the substrate 60. The plurality of light sources 76 have a spectral output corresponding to absorption bands of
25 fluorophores used to provide the optical indication. A color filter 78 is incorporated over each of the plurality of optical detectors 72 to screen out light emanating from the plurality of light sources 76.

To speed up the hybridization and de-hybridization
30 processes, each of the plurality of binding sites 62 has a respective one of a plurality of transparent electrodes 80 integrated in proximity thereto. The transparent electrodes 80 generate electric fields for field-enhanced hybridization and de-hybridization. The transparent

0 electrodes 80 are individually addressable for self-addressing and self-assembly purposes. The integrated molecular detection chip can further include a polymer membrane at each of the plurality of binding sites 62 to aid in binding molecules thereto.

5 In operation, appropriate DNA sequences hybridize onto selective ones of the plurality of binding sites 62 using either conventional, field-assisted, or thermally-assisted hybridization. After hybridization, unwanted sequences with only a partial binding are de-hybridized
10 using field enhancement or thermal desorption. The plurality of light sources 76 are illuminated, and the fluorescence of each of the plurality of binding sites 62 is read by the plurality of optical detectors 72. Phase-sensitive detecting techniques can be incorporated by
15 modulating a drive current to each of the plurality of optical detectors 72. These techniques are beneficial to enhance sensitivity of the detection.

The hybridized sites can then be detected to determine specific nucleotide sequences within the DNA
20 sample. The molecular detection chip can then be fully de-hybridized using chemical, thermal, or field-assisted means so that the hybridization and detection process can be repeated.

Thus, there has been described herein a concept, as
25 well as several embodiments including preferred embodiments of an integrated optical molecular detection device and a method therefor.

Because the various embodiments of the present invention integrate a binding site, a light source, and an
30 optical detector on a single substrate, they provide a significant improvement in that a fully integrated molecular detection device is produced.

Additionally, the various embodiments of the present invention as herein-described include a transparent

0 electrode proximate to each binding site to provide field-assisted hybridization and de-hybridization. The transparency of the electrode allows an optical indication of binding to be both illuminated and detected through the electrode.

5 It will be apparent to those skilled in the art that the disclosed invention may be modified in numerous ways and may assume many embodiments other than the preferred form specifically set out and described above.

10 Accordingly, it is intended by the appended claims to cover all modifications of the invention which fall within the true spirit and scope of the invention.

What is claimed is:

0

Claims

1. An integrated molecular detection device comprising:
5 a substrate which defines a binding site for receiving a molecular receptor;
a light source integrated in the substrate, the light source for illuminating the binding site through the substrate to produce an optical indication of a molecule hybridized to the molecular receptor; and
10 an optical detector integrated in the substrate, the optical detector for detecting the optical indication through the substrate.
2. The integrated molecular detection device of
15 claim 1 wherein the substrate is substantially transparent.
3. The integrated molecular detection device of claim 1 wherein the substrate is formed of glass.
- 20 4. The integrated molecular detection device of claim 1 wherein the substrate defines a first side on which the binding site is defined and a second side opposite to the first side on which the light source is integrated.
- 25 5. The integrated molecular detection device of claim 1 wherein the molecular receptor includes a chain of at least one nucleotide, and wherein the molecule includes a complementary chain of at least one nucleotide.

0 6. A method of detecting hybridization of a molecule
to a molecular receptor, the method comprising the steps
of:

 providing a substrate which defines a binding site
for receiving the molecular receptor;

5 illuminating the binding site with a light source
integrated in the substrate, the binding site being
illuminated through the substrate to produce an optical
indication of a molecule hybridized to the molecular
receptor; and

10 detecting the optical indication through the
substrate by an optical detector integrated in the
substrate.

 7. The method of claim 6 wherein the optical
15 indication is detected from the second side of the
substrate.



 8. The method of claim 7 wherein the optical
indication is detected by a photodiode fabricated on the
20 second side of the substrate.

 9. The method of claim 7 further comprising the step
of screening the optical detector from light which
illuminates the binding site.


25 -

 10. The method of claim 6 wherein the optical
indication is detected through a transparent electrode
proximate to the binding site.

1/3

**FIG.1****FIG.2**

2/3

**FIG.3**

3/3




FIG. 4




FIG. 5

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US97/05534

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : Please See Extra Sheet.

US CL : Please See Extra Sheet.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 435/6, 287.2, 288.7, 91.2; 436/ 169; 422/58, 82.05, 82.09; 204/403, 222, 400

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

Please See Extra Sheet.

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X ----- P, Y	US, 5,580,794 A (ALLEN) 03 December 1996, see entire document.	1-7 ----- 8-10
P, Y	US 5,527,670 A (STANLEY) 18 June 1996, see abstract.	1-10
Y	US 4,915,812 A (PARCE et al.) 10 April 1990, see entire document.	1-10

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

* Special categories of cited documents:	*T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z*	document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means		
P document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

12 MAY 1997

Date of mailing of the international search report

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

DIANNE REES

Telephone No. (703) 308-0196

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US97/05534

A. CLASSIFICATION OF SUBJECT MATTER:

IPC (6):

C12Q 1/68, C12M 1/00, 1/40; C12P 19/34; G01N 21/77, 21/00, 21/29, 21/27, 27/26; C25D 17/00

A. CLASSIFICATION OF SUBJECT MATTER:

US CL :

435/6, 287.2, 288.7, 91.2; 436/ 169; 422/58, 82.05, 82.09; 204/403, 222, 400

B. FIELDS SEARCHED

Electronic data bases consulted (Name of data base and where practicable terms used):

APS, BIOSIS, BIOTECHABS, BIOTECHDS, BIOBUSINESS, CABA, CAPLUS, CANCERLIT, DRUGU, EMBASE, EUROPATFULL, IFIPAT, JAPIO, MEDLINE, USPATFULL, WPIDS, SCISEARCH, TOXLINE, TOXLIT
search terms: hybridization, hybridisation, arrays, ligand, receptor, nucleic acids, oligonucleotides, DNA, probes, polynucleotides, antibody, antigen, light source, beam, laser, detector, photodetector, electrodes, photodiode, LED, transparent electrodes, glass electrodes